

INFUSION PUMP ManoPump iV1



PRACTICAL, ERGONOMIC AND EFFICIENT:

- Small and light (1.45 kg)
- Kennel mount and IV stand support included
- High-performance battery (up to 10 hours run time)
- Large touchscreen (4.3"-10.75 cm) for a clear diplay of parameters including infusion time left
- Many settings available such as:
 - ✓ Overall infusion volume
 - ✓ Requested flow
 - ✓ Infusion total time
- High sensitivity of settings (bubbles and occlusion pressure)
- Transfusion compatible





Application fields of an infusion pump.



Intensive care

A continuous infusion is vital for any dehydrated patient.

The flow rate is conditioned by the required volume and the duration of the infusion:

1 - Initial deficit to compensate

Deficit to compensate (liters) = Weight (Kg) \times % of dehydration / 100 Example: 3 kg cat dehydrated by 15% -> Q = 3 \times 0.15 = 0.45 | (450 ml)

2 - Maintenance need:

Large dog = 60 ml/kg/24h - Medium dog = 50 ml/kg/24h - Small dog or cat = 40 ml/kg/24h

3 - Loss:

4 ml/kg vomiting - 200 ml/kg diarrhea - 1 – 2 ml/kg urinating

Surgery

A correctly perfused animal will wake up faster (no hypovolemia), moreover, the kidney failure risk is considerably reduced.

Recommendation for intraoperative infusion flow rates:

Low blood loss: 10ml/kg/hNormal blood loss: 15ml/kg/hHigh blood loss: 20ml/kg/h

During postoperative process, the infusion must be maintained until the patient wakes up.

The ManoPump iV1 infusion pump is equipped with a battery running up to 10 hours:

- √ to monitor the patient before, during and after the surgery
- √ to allow uninterrupted operation even in case of power shortages
- √ to be used at the clinic as well as outside (home-based care, transportation)

ManoPump iV1 technical data:

▶ Accumulated volume	From 0.1 to 9999 ml
▶ Touchscreen	4.3'' (10.75 cm)
▶ Infusion time left	Yes
▶ Flow	From 0.1 to 2000 ml/h
▶ Modes	Flow and volume • Overall length and volume • Overall lentgh and flow • Body mass • Saved modes • Micro mode
▶ Accuracy	+/- 5%
▶ Air bubble detection	20, 50, 100, 200, 400,800 µl
▶ Occlusion settings	5 levels (50, 150, 300, 600, 900 mmHG)
▶ Entry capacity	Up to 2000
▶ Data review	5000
▶ Quick setting use	Access to the 20 latest settings
▶ Protection classification	IP44
▶ Dimensions and weight	13x9x14 cm - 1.45 kg
▶ Operating life	10h at 25 ml/h
▶ Power	100-240V, 50-60 Hz
▶ Safety and operating alarms	Yes
▶ Self-diagnostic	Yes
► Mounting system	IV stand support and kennel mount included







IV stand support

Kennel mount



22 rue Charles de Gaulle 22100 Lanvallay - France Tel. +33 (0) 2 96 85 86 76

export@manomedical.com

www.manomedical.com